

TERMINAL KITS

Terminal & Tool Organizer



A 21 compartment, metal box with a sturdy plastic tray insert and a metal latch. This Terminal Kit Box provides organized storage for solder less terminals, connectors and your crimping tool. The lid features a matrix chart for part number identification.

PART NO	COLOR	SIZE	DESCRIPTION
P298-TKBOX	Black	13.5" x 9.5" x 2"	TERMINAL KIT BOX

HVAC Electrical Repair Kit

TOTALINE HVAC Electrical Repair Kit contains 400 of the most popular terminals & connectors as well as a crimping tool for the 22-10 AWG wire ranges. The terminals are stored in a metal terminal box with a sturdy plastic 21 compartment insert and a metal latch for securing the lid. TOTALINE graphics appear on the label set, with a matrix chart on the inside lid describing the parts, including illustrations and individual TOTALINE re-order part numbers.

PART NO	COLOR	SIZE	DESCRIPTION
P298-HVACKIT	Black	13.75" x 9" x 2.25"	HVAC ELECTRICAL REPAIR KIT

Solderless Terminal Kit



An economical 18 compartment, plastic kit box contains 450 of the most popular TOTALINE solderless terminals and connectors. TOTALINE graphics appear on the label set, with a matrix chart on the inside lid describing the parts, illustrations & individual TOTALINE re-order part numbers.

PART NO	COLOR	SIZE	DESCRIPTION
P298-TERMKIT450	CLEAR PLASTIC	13.1" x 9" x 2.3"	SOLDERLESS TERMINAL KIT

CABLE TIES Natural

Standard Ties

- versatile, multiple purpose



PART NO	MINIMUM TENSILE UN-LOCKING STRENGTH	MAXIMUM BUNDLE DIAMETER	WIDTH	LENGTH	QTY/PKG
P298-TF3	18 lbs. (8.2 kg)	7/8" (22.2 mm)	.095" (2.4 mm)	4.1" (10.4 cm)	100
P298-TF3B	18 lbs. (8.2 kg)	7/8" (22.2 mm)	.095" (2.4 mm)	4.1" (10.4 cm)	1000
P298-TF4	40 lbs. (18.1 kg)	1-7/16" (36.5 mm)	.140" (3.5 mm)	5.8" (14.8 cm)	100
P298-TF4B	40 lbs. (18.1 kg)	1-7/16" (36.5 mm)	.140" (3.5 mm)	5.8" (14.8 cm)	1000
P298-TF5	50 lbs. (22.7 kg)	1-7/8" (47.6 mm)	.180" (4.5 mm)	7.5" (19.2 cm)	100
P298-TF5B	50 lbs. (22.7 kg)	1-7/8" (47.6 mm)	.180" (4.5 mm)	7.5" (19.2 cm)	1000
P298-TF6	50 lbs. (22.7 kg)	3-1/16" (77.7 mm)	.180" (4.5 mm)	11.3" (28.5 cm)	50
P298-TF6B	50 lbs. (22.7 kg)	3-1/16" (77.7 mm)	.180" (4.5 mm)	11.3" (28.5 cm)	1000
P298-TF8	50 lbs. (22.7 kg)	4-1/8" (104.7 mm)	.180" (4.5 mm)	14.5" (36.9 cm)	50
P298-TF8B	50 lbs. (22.7 kg)	4-1/8" (104.7 mm)	.180" (4.5 mm)	14.5" (36.9 cm)	1000

Heavy Duty Ties

- extra strong for more demanding applications

PART NO	MINIMUM TENSILE UN-LOCKING STRENGTH	MAXIMUM BUNDLE DIAMETER	WIDTH	LENGTH	QTY/PKG
P298-TF7	120 lbs. (54.4 kg)	4-1/16" (103.1 mm)	.300" (7.6 mm)	15" (38.3 cm)	25
P298-TF7B	120 lbs. (54.4 kg)	4-1/16" (103.1 mm)	.300" (7.6 mm)	15" (38.3 cm)	500

Heavy Duty Duct Straps

for use with flexible air ducts and air connectors



PART NO	MINIMUM TENSILE UN-LOCKING STRENGTH	MAXIMUM BUNDLE DIAMETER	WIDTH	LENGTH	QTY/PKG
P298-TF12	175 lbs. (79.3 kg)	11" (279.4 mm)	.340" (8.6 mm)	37.3" (94.6 cm)	25
P298-TF48	175 lbs. (79.3 kg)	14.5" (368.3mm)	.340" (8.6 mm)	48.5" (123.1 cm)	25
P298-TF488	175 lbs. (79.3 kg)	14.5" (368.3mm)	.340" (8.6 mm)	48.5" (123.1 cm)	(Gray)25

Mounting Cable Ties • one piece for quick, simple bundling and mounting

PART NO	MINIMUM TENSILE UN-LOCKING STRENGTH	MAXIMUM BUNDLE DIAMETER	WIDTH	LENGTH	QTY/PKG
P298-TF3H	30 lbs. (13.6 kg)	1-1/4" (31.7 mm)	.138" (3.5 mm)	5.8" (14.9 cm)	100
P298-TF3HB	30 lbs. (13.6 kg)	1-1/4" (31.7 mm)	.138" (3.5 mm)	5.8" (14.9 cm)	1000
P298-TF5H	50 lbs. (22.7 kg)	1-3/4" (44.4 mm)	.177" (4.4 mm)	8.0" (20.3 cm)	50
P298-TF5HB	50 lbs. (22.7 kg)	1-3/4" (44.4 mm)	.177" (4.4 mm)	8.0" (20.3 cm)	1000
P298-TF7H	120 lbs. (54.4 kg)	4-1/16" (103.1 mm)	.298" (7.5 mm)	15.7" (39.8 cm)	50
P298-TF7HB	120 lbs. (54.4 kg)	4-1/16" (103.1 mm)	.298" (7.5 mm)	15.7" (39.8 cm)	500

CABLE TIES Weatherproof Black

Standard Ties

• versatile, multiple purpose



PART NO	MINIMUM TENSILE UNLOCKING STRENGTH	MAXIMUM BUNDLE DIAMETER	WIDTH	LENGTH	QTY/PKG
P298-TF3X	18 lbs. (8.2 kg)	7/8" (22.2 mm)	.095" (2.4 mm)	4.1" (10.4 cm)	100
P298-TF3XB	18 lbs. (8.2 kg)	7/8" (22.2 mm)	.095" (2.4 mm)	4.1" (10.4 cm)	1000
P298-TF4X	40 lbs. (18.1 kg)	1-7/16" (36.5 mm)	.140" (3.5 mm)	5.8" (14.8 cm)	100
P298-TF4XB	40 lbs. (18.1 kg)	1-7/16" (36.5 mm)	.140" (3.5 mm)	5.8" (14.8 cm)	1000
P298-TF5X	50 lbs. (22.7 kg)	1-7/8" (47.6 mm)	.180" (4.5 mm)	7.5" (19.2 cm)	100
P298-TF5XB	50 lbs. (22.7 kg)	1-7/8" (47.6 mm)	.180" (4.5 mm)	7.5" (19.2 cm)	1000
P298-TF6X	50 lbs. (22.7 kg)	3-1/16" (77.7 mm)	.180" (4.5 mm)	11.3" (28.5 cm)	50
P298-TF6XB	50 lbs. (22.7 kg)	3-1/16" (77.7 mm)	.180" (4.5 mm)	11.3" (28.5 cm)	1000
P298-TF8X	50 lbs. (22.7 kg)	4-1/8" (104.7 mm)	.180" (4.5 mm)	14.5" (36.9 cm)	50
P298-TF8XB	50 lbs. (22.7 kg)	4-1/8" (104.7 mm)	.180" (4.5 mm)	14.5" (36.9 cm)	1000

Heavy Duty Ties

• extra strong for more demanding applications



PART NO	MINIMUM TENSILE UN-LOCKING STRENGTH	MAXIMUM BUNDLE DIAMETER	WIDTH	LENGTH	QTY/PKG
P298-TF7X	120 lbs. (54.4 kg)	4-1/16" (103.1 mm)	.300" (7.6 mm)	15" (38.3 cm)	25
P298-TF7XB	120 lbs. (54.4 kg)	4-1/16" (103.1 mm)	.300" (7.6 mm)	15" (38.3 cm)	500

Heavy Duty Duct Straps

• for use with flexible air ducts and air connectors



PART NO	MINIMUM TENSILE UNLOCKING STRENGTH	MAXIMUM BUNDLE DIAMETER	WIDTH	LENGTH	QTY/PKG
P298-TF12X	175 lbs. (79.3 kg)	11" (279.4 mm)	.340" (8.63 mm)	37.3" (94.6 cm)	25
P298-TF48X	175 lbs. (79.3 kg)	14.5" (368.3 mm)	.340" (8.63 mm)	48.5" (123.1 cm)	25

Mounting Cable Ties

- one piece for quick, simple bundling and mounting



PART NO	MINIMUM TENSILE UN-LOCKING STRENGTH	MAXIMUM BUNDLE DIAMETER	WIDTH	LENGTH	QTY/PKG
P298-TF3HX	30 lbs. (13.6 kg)	1-1/4" (31.7 mm)	.138" (3.50 mm)	5.8" (14.9 cm)	100
P298-TF3HXB	30 lbs. (13.6 kg)	1-1/4" (31.7 mm)	.138" (3.50 mm)	5.8" (14.9 cm)	1000
P298-TF5HX	50 lbs. (22.7 kg)	1-3/4" (44.4 mm)	.177" (4.49 mm)	8.0" (20.3 cm)	50
P298-TF5HXB	50 lbs. (22.7 kg)	1-3/4" (44.4 mm)	.177" (4.49 mm)	8.0" (20.3 cm)	1000
P298-TF7HX	120 lbs. (54.4 kg)	4-1/16" (103.1 mm)	.298" (7.56 mm)	15.7" (39.8 cm)	50
P298-TF7HXB	120 lbs. (54.4 kg)	4-1/16" (103.1 mm)	.298" (7.56 mm)	15.7" (39.8 cm)	500

SHRINK TUBING

DWA Dual Wall Heat Shrinkable Tubing



Flame-retardant, adhesive-lined, (semi-rigid) Olyoletin

FEATURES / BENEFITS

- Tubing environmentally seals and protects components and splices
- DWA has a high shrink ratio, only a few sizes are needed to cover a wide range of splice and component diameters
- Adhesive bonds to a wide variety of plastics, rubber, & metals, including polyethylene, neoprene, & steel
- Offers rugged protection against abrasion, vibration, and flexing
- Extended temperature range

PRODUCT CHARACTERISTICS

Shrink Ratio Approximately: 4:1

Minimum shrink temperature: 230°F (110°C)

Continuous operating temperature: -40°F to 266°F (-40°C to 130°C)

PART NO	DIAMETER BEFORE SHRINKING	SUITABLE FOR THIS DIAMETER RANGE	LENGTH	QTY/PKG
P298-DWA1	.225"	(1/16"-3/16")	6"	6
P298-DWA2	.293"	(3/16"-1/4")	6"	6
P298-DWA3	.427"	(1/4"-3/8")	6"	4
P298-DWA4	.700"	(1/2"-5/8")	6"	2

TEW Thermoplastic Equipment Wire • 100' Spools



- Material is TEW bare copper strand – voltage: 600 volts
- Temperature rating: -22°F to 221°F (-30°C to 105°C)
- UL Listed & CSA approved
- Spooled on metal spools
- Totaline label with part description and part nomenclature

18 AWG (16 Strands) TEW Wire 100' Spools

PART NO	DESCRIPTION
P298-TEW18/16-BLACK	18 AWG TEW Wire - Black
P298-TEW18/16-WHITE	18 AWG TEW Wire - White
P298-TEW18/16-RED	18 AWG TEW Wire - Red
P298-TEW18/16-BLUE	18 AWG TEW Wire - Blue
P298-TEW18/16-GREEN	18 AWG TEW Wire - Green

16AWG (26 Strands) TEW Wire 100' Spools

PART NO	DESCRIPTION
P298-TEW16/26-BLACK	16 AWG TEW Wire - Black
P298-TEW16/26-WHITE	16 AWG TEW Wire - White
P298-TEW16/26-RED	16 AWG TEW Wire - Red
P298-TEW16/26-BLUE	16 AWG TEW Wire - Blue
P298-TEW16/26-GREEN	16 AWG TEW Wire - Green

14 AWG (41 Strands) TEW Wire 100' Spools

PART NO	DESCRIPTION
P298-TEW14/41-BLACK	14 AWG TEW Wire - Black
P298-TEW14/41-WHITE	14 AWG TEW Wire - White
P298-TEW14/41-RED	14 AWG TEW Wire - Red
P298-TEW14/41-BLUE	14 AWG TEW Wire - Blue
P298-TEW14/41-GREEN	14 AWG TEW Wire - Green

12 AWG (65 Strands) TEW Wire 100' Spools

PART NO	DESCRIPTION
P298-TEW12/65-BLACK	12 AWG TEW Wire - Black
P298-TEW12/65-WHITE	12 AWG TEW Wire - White
P298-TEW12/65-RED	12 AWG TEW Wire - Red
P298-TEW12/65-BLUE	12 AWG TEW Wire - Blue
P298-TEW12/65-GREEN	12 AWG TEW Wire - Green


10 AWG (104 Strands) TEW Wire 100' Spools

PART NO	DESCRIPTION
P298-TEW10/104-BLACK	10 AWG TEW Wire - Black
P298-TEW10/104-WHITE	10 AWG TEW Wire - White
P298-TEW10/104-RED	10 AWG TEW Wire - Red
P298-TEW10/104-BLUE	10 AWG TEW Wire - Blue
P298-TEW10/104-GREEN	10 AWG TEW Wire - Green


WIRING ACCESSORIES

Halar & Tefzel Cable Ties

HALAR TIES feature low smoke density and high flame resistance and are ideal for plenum areas where smoke generation is a concern.




PART NO	MINIMUM TENSILE UN-LOCKING STRENGTH	MAXIMUM BUNDLE DI-AMETER	WIDTH	LENGTH	QTY/PKG
P298-CT0418HL	18 lbs. (8.2 kg)	7/8" (22.2 mm)	.094" (2.4 mm)	4.0" (10.1 cm)	100
P298-CT0750HL	50 lbs. (22.7 kg)	2.0" (50.8 mm)	.178" (4.5 mm)	8.0" (20.3 cm)	100
P298-CT0418TZ	12 lbs. (5.4 kg)	7/8" (22.2 mm)	.094" (2.4 mm)	4.0" (10.1 cm)	100
P298-CT0750TZ	50 lbs. (22.7 kg)	1-7/8" (47.6 mm)	.178" (4.5 mm)	7.0" (17.7 cm)	100



Cable Tie Mounting Base

PART NO	DIMENSIONS in (mm)	QTY/PKG
P298-CTMB	1" x 1" (25.1 x 25.1)	25




Self-Stripping Tap Connectors

PART NO	WIRE RANGE AWG (mm2)	QTY/PKG
P298-SSTCR	22-16 (0.5-1.0) RED	25
P298-SSTCB	18-14 (.75-2.5) BLUE	25
P298-SSTCY	12-10 (4.0-6.0) YELLOW	20

Cable Clamps • Natural Nylon




PART NO	MAXIMUM BUNDLE DIA.		QTY/PKG
	in	(mm)	
P298-CC0125	1/8"	-3.18	50
P298-CC01875	3/16"	-4.76	50
P298-CC0250	1/4"	-6.35	45
P298-CC0375	3/8"	-9.53	40
P298-CC0500	1/2"	-12.7	35
P298-CC0750	3/4"	-19.1	20
P298-CC01000	1"	-25.4	15




Compressor Hook-up Lead Kit

PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-LEADS-10	.250 (6.35)	10 (6.0)	3-8" leads with flags 3- heat shrinkable butt connectors



Compressor Terminal

PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-COM1208	.250 (6.35)	12-8 (4.0-6.75)	20



Closed End Connectors • Nylon Insulated

PART NO	WIRE RANGE-AWG	QTY/PKG
P298-CES2214	22-14 (0.5-2.5)	50
P298-CES1810	18-10 (1.0-6.0)	40




Twist-On Wire Connectors

UL Listed/CSA Approved 221°F/105°C (Available in Blister Boxes, TOTALINE Boxes or Bulk Packs)

PART NO	AWG	(mm2)	COLOR/VOLTAGE	QTY/PKG
P298-WC/GREY	22-14 (0.5-2.5)	Min. 2 # 22	GREY	100 (Blister Box)
P298-WC/GREY/M	22-14 (0.5-2.5)	Max. 2 #16	300 Volt	1,000 (Bulk Pack)
P298-29	22-14 (0.5-2.5)	Min. 2 #18	BLUE	100 (Blister Box)
P298-29B	22-14 (0.5-2.5)	Max. 3 #16	300 Volt	100 (TOTALINE Box)
P298-WC/BLUE/M	22-14 (0.5-2.5)	--	--	1,000 (Bulk Pack)
P298-31	22-14 (0.5-2.5)	Min. 2 #18	ORANGE	75 (Blister Box)
P298-31B	22-14 (0.5-2.5)	Max. 2 #14	600 Volt	100 (TOTALINE Box)
P298-WC/ORANGE/D	22-14 (0.5-2.5)	--	--	500 (Bulk Pack)
P298-33	18-10 (1.0-6.0)	Min. 3 #18	YELLOW	
P298-33B	18-10 (1.0-6.0)	Max. 4 #14 and 1 #18	600 Volt	100 (TOTALINE Box)
P298-WC/YELLOW/D	18-10 (1.0-6.0)	--	--	500 (Bulk Pack)
P298-35	18-8 (1.0-8.0)	Min. 2 #14	RED	35 (Blister Box)
P298-35B	18-8 (1.0-8.0)	Max. 4 #12	600 VOLT	100 (TOTALINE Box)
P298-WC/RED/D	18-8 (1.0-8.0)	--	--	500 (Bulk Pack)

Ring Terminals

• Vinyl Insulated




PART NO	WIRE RANGE AWG (mm2)	in / ga	(mm)	QTY/PKG
P298-RR6	22-18 (0.5-1.0) RED	#6	-3.5	100
P298-RR8	22-18 (0.5-1.0) RED	#8	-4.16	100
P298-RR10	22-18 (0.5-1.0) RED	#10	-4.82	100
P298-RR0250	22-18 (0.5-1.0) RED	1/4"	-6.35	75
P298-RR0375	22-18 (0.5-1.0) RED	3/8"	-9.53	65
P298-BR6	16-14 (1.5-2.5) BLUE	#6	-3.5	100
P298-BR8	16-14 (1.5-2.5) BLUE	#8	-4.16	100
P298-BR10	16-14 (1.5-2.5) BLUE	#10	-4.82	100
P298-BR0250	16-14 (1.5-2.5) BLUE	1/4"	-6.35	75
P298-BR0315	16-14 (1.5-2.5) BLUE	5/16"	-7.94	65
P298-BR0375	16-14 (1.5-2.5) BLUE	3/8"	-9.53	65
P298-YR6	12-10 (4.0-6.0) YELLOW	#6	-3.5	75
P298-YR8	12-10 (4.0-6.0) YELLOW	#8	-4.16	75
P298-YR10	12-10 (4.0-6.0) YELLOW	#10	-4.82	75
P298-YR0250	12-10 (4.0-6.0) YELLOW	1/4"	-6.35	60
P298-YR0315	12-10 (4.0-6.0) YELLOW	5/16"	-7.94	60
P298-YR0375	12-10 (4.0-6.0) YELLOW	3/8"	-9.53	60
P298-YR0500	12-10 (4.0-6.0) YELLOW	1/2"	-12.7	40

Heavy Duty Ring Terminals • Vinyl Insulated

PART NO	WIRE RANGE AWG (mm2)	in / ga	(mm)	QTY/PKG
P298-8R0250	8 (8.0) RED	1/4"	-6.35	20
P298-8R0315	8 (8.0) RED	5/16"	-7.94	20
P298-8R0375	8 (8.0) RED	3/8"	-9.53	20
P298-8R0500	8 (8.0) RED	1/2"	-12.7	15
P298-6R0250	6 (14.0) BLUE	1/4"	-6.35	15
P298-6R0315	6 (14.0) BLUE	5/16"	-7.94	15
P298-6R0375	6 (14.0) BLUE	3/8"	-9.53	15
P298-6R0500	6 (14.0) BLUE	1/2"	-12.7	10

Block Spade Terminals

• Vinyl Insulated



PART NO	WIRE RANGE AWG (mm2)	in / ga	(mm)	QTY/PKG
P298-RS6	22-18 (0.5-1.0) RED	#6	-3.5	100
P298-RS8	22-18 (0.5-1.0) RED	#8	-4.16	100
P298-RS10	22-18 (0.5-1.0) RED	#10	-4.82	100
P298-BS6	16-14 (1.5-2.5) BLUE	#6	-3.5	100
P298-BS8	16-14 (1.5-2.5) BLUE	#8	-4.16	100
P298-BS10	16-14 (1.5-2.5) BLUE	#10	-4.82	100
P298-YS6	12-10 (4.0-6.0) YELLOW	#6	-3.5	75
P298-YS8	12-10 (4.0-6.0) YELLOW	#8	-4.16	75
P298-YS10	12-10 (4.0-6.0) YELLOW	#10	-4.82	75

Butt Connectors

• Vinyl Insulated



PART NO	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RBS	22-18 (0.5-1.0) RED	100
P298-BBS	16-14 (1.5-2.5) BLUE	100
P298-YBS	12-10 (4.0-6.0) YELLOW	75


Heat Shrinkable Butt Connectors

• Environmentally Sealed



PART NO	WIRE RANGE AWG (mm2)	QTY/PKG
P298-HSRBS	22-18 (0.5-1.0) RED	10
P298-HSBBS	16-14 (1.5-2.5) BLUE	10
P298-HSYBS	12-10 (4.0-6.0) YELLOW	8


Double Male-Female Adapters



PART NO	TAB WIDTH in (mm)	QTY/PKG
P298-77250	.250 (6.35) (Piggyback)	30
P298-7MMF187	.187 (4.75) (Flat)	40
P298-7MMF250	.250 (6.35) (Flat)	40


Multi-Stack Disconnects

• Vinyl Insulated



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RQDFM	.250 (6.35)	22-18 (0.5-1.0) RED	30
P298-BQDFM	.250 (6.35)	16-14 (1.5-2.5) BLUE	30


Double Male Quick Disconnects



PART NO	TAB WIDTH in (mm)	QTY/PKG
P298-DMD250	.250 (6.35)	10

Female Flag Quick Disconnects

• Uninsulated



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RF187	.187 (4.75)	22-18 (0.5-1.0)	50
P298-RF250	.250 (6.35)	22-18 (0.5-1.0)	50
P298-BF187	.187 (4.75)	16-14 (1.5-2.5)	50
P298-BF250	.250 (6.35)	16-14 (1.5-2.5)	50
P298-YF250	.250 (6.35)	12-10 (4.0-6.0)	40

Female Flag Quick Disconnects

• Fully Insulated Nylon



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RFF1187	.187 (4.75)	22-18 (0.5-1.0)	30
P298-RFF1250	.250 (6.35)	RED	30
P298-BFF1187	.187 (4.75)	16-14 (1.5-2.5)	30
P298-BFF1250	.250 (6.35)	BLUE	30

Compressors,
Chillers, Condensers

Motors

Electrical

Heating
Components

Indoor Air
Quality

Thermostats

Oils &
Chemicals

Accessories, Supplies
& Commodities

Tools &
Instruments

Refrigeration


High Temperature Ring Terminals

900°F / 482°C Continuous Temperature Rating. Steel Construction.
Nickel Plating




PART NO	WIRE RANGE AWG (mm2)	in / ga	(mm)	QTY/PKG
P298-HTRR6	22-18 (0.5-1.0)	#6	-3.5	100
P298-HTRR10	22-18 (0.5-1.0)	#10	-4.82	100
P298-HTBR6	16-14 (1.5-2.5)	#6	-3.5	100
P298-HTBR10	16-14 (1.5-2.5)	#10	-4.82	100
P298-HTBR0250	16-14 (1.5-2.5)	1/4"	-6.35	75
P298-HTYR6	12-10 (4.0-6.0)	#6	-3.5	75
P298-HTYR10	12-10 (4.0-6.0)	#10	-4.82	75
P298-HTYR0250	12-10 (4.0-6.0)	1/4"	-6.35	60

High Temperature Butt Connectors



PART NO	WIRE RANGE AWG (mm2)	QTY/PKG
P298-HTRBS	22-18 (0.5-1.0)	100
P298-HTBBS	16-14 (1.5-2.5)	100
P298-HTYBS	12-10 (4.0-6.0)	75


High Temperature Female Quick Disconnect



PART NO	WIRE RANGE AWG (mm2)	in / ga	(mm)	QTY/PKG
P298-HTBQDF250	16-14 (1.5-2.5)	0.25	-6.35	100

Quick Disconnect Terminals


• Vinyl Insulated • Female



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RQDF110	.110 (2.79)	22-18 (0.5-1.0) RED	100
P298-RQDF187	.187 (4.75)	22-18 (0.5-1.0) RED	100
P298-RQDF250	.250 (6.35)	22-18 (0.5-1.0) RED	100
P298-BQDF110	.110 (2.79)	16-14 (1.5-2.5) BLUE	100
P298-BQDF187	.187 (4.75)	16-14 (1.5-2.5) BLUE	100
P298-BQDF250	.250 (6.35)	16-14 (1.5-2.5) BLUE	100
P298-YQDF250	.250 (6.35)	12-10 (4.0-6.0) YELLOW	75

Quick Disconnect Terminals

• Vinyl Insulated • Male



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RQDM187	.187 (4.75)	22-18 (0.5-1.0) RED	100
P298-RQDM250	.250 (6.35)	22-18 (0.5-1.0) RED	100
P298-BQDM187	.187 (4.75)	16-14 (1.5-2.5) BLUE	100
P298-BQDM250	.250 (6.35)	16-14 (1.5-2.5) BLUE	100
P298-YQDM250	.250 (6.35)	12-10 (4.0-6.0) YELLOW	75


Mating Fully Insulated Quick Disconnects

• Nylon Insulated • Female



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RQDFFI187	.187 (4.75)	22-18 (0.5-1.0) RED	40
P298-RQDFFI250	.250 (6.35)	22-18 (0.5-1.0) RED	40
P298-BQDFFI187	.187 (4.75)	16-14 (1.5-2.5) BLUE	40
P298-BQDFFI250	.250 (6.35)	16-14 (1.5-2.5) BLUE	40
P298-YQDFFI250	.250 (6.35)	12-10 (4.0-6.0) YELLOW	30

High Temperature Spade Terminals




PART NO	WIRE RANGE AWG (mm2)	in / ga	(mm)	QTY/PKG
P298-HTRS10	22-18 (0.5-1.0)	#10	-4.82	100
P298-HTBS10	16-14 (1.5-2.5)	#10	-4.82	100
P298-HTYS10	12-10 (4.0-6.0)	#10	-4.82	75

High Temperature Female Flag Disconnect



PART NO	WIRE RANGE AWG (mm2)	in / ga	(mm)	QTY/PKG
P298-HTBFF250	16-14 (1.5-2.5)	0.25	-6.35	75

High Temperature Male Quick Disconnect



PART NO	WIRE RANGE AWG (mm2)	in / ga	(mm)	QTY/PKG
P298-HTBQDM250	16-14 (1.5-2.5)	0.25	-6.35	100

Mating Fully Insulated Quick Disconnects

• Nylon Insulated • Male



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RQDMFI187	.187 (4.75)	22-18 (0.5-1.0) RED	40
P298-RQDMFI250	.250 (6.35)	22-18 (0.5-1.0) RED	40
P298-BQDMFI187	.187 (4.75)	16-14 (1.5-2.5) BLUE	40
P298-BQDMFI250	.250 (6.35)	16-14 (1.5-2.5) BLUE	40
P298-YQDMFI250	.250 (6.35)	12-10 (4.0-6.0) YELLOW	30


Snap Plugs

• Vinyl Insulated




PART NO	WIRE RANGE AWG (mm2)	in	(mm)	QTY/PKG
P298-RBM157	22-18 (0.5-1.0) RED	0.157	3.99	80
P298-RBM176	22-18 (0.5-1.0) RED	0.176	4.47	80
P298-BBM157	16-14 (1.5-2.5) BLUE	0.157	3.99	80
P298-BBM176	16-14 (1.5-2.5) BLUE	0.176	4.47	80
P298-YBM157	12-10 (4.0-6.0) YELLOW	0.157	3.99	60
P298-YBM176	12-10 (4.0-6.0) YELLOW	0.176	4.47	60

Snap Plug Receptacles



PART NO	WIRE RANGE AWG (mm2)	in	(mm)	QTY/PKG
P298-RBFFI157	22-18 (0.5-1.0) RED	0.157	3.99	40
P298-RBFFI176	22-18 (0.5-1.0) RED	0.176	4.47	40
P298-BBFFI157	16-14 (1.5-2.5) BLUE	0.157	3.99	40
P298-BBFFI176	16-14 (1.5-2.5) BLUE	0.176	4.47	40
P298-YBFFI157	12-10 (4.0-6.0) YELLOW	0.157	3.99	30
P298-YBFFI176	12-10 (4.0-6.0) YELLOW	0.176	4.47	30

Double Female Snap Plug Receptacles



PART NO	Dia.in	(mm)	QTY/PKG
P298-DBR157	0.157	3.99	40
P298-DBR176	0.176	4.47	40