

Totaline® Wireless Non-Programmable Thermostat



The Totaline® P360-0320 Non-Programmable Thermostat is wireless and utilizes RedLINK technology, so the thermostat can be installed anywhere. Because the wiring is done at an Equipment Interface Module by the equipment, adding multi-stage systems or cooling is a breeze. The P360-0320 thermostat provides electronic control of 24Vac conventional and heat pump systems.

Features:

- Non-Programmable Thermostat
- Easy to read backlit digital display
- Easy-Access Battery Replacement - Flip-out door allows for easy battery replacement without removing or disassembling the thermostat.
- Large, Clear Backlit Digital Display - Easy to read in various lighting conditions.
- Precise Comfort Control - Maintains consistent comfort to the highest level of accuracy.
- RedLINK Wireless Enabled - Re-locate a thermostat, upgrade equipment, add temperature zoning quickly and easily without running wires.
- Can display outdoor temperature and humidity
- 2 month low battery warning, 1 year battery life
- 5-Year Limited Warranty

Specifications:

- Options: Fan Control, Wireless, Auto Changeover
- Stages: 3 Heat/2 Cool Heat Pump, 2 Heat/2 Cool
- Amperage: 0.6-1
- User Interface: Push Button
- Power Method: Battery
- Application: Heat Pump, Multi-Stage (Heat & Cool)
- Voltage: Low voltage
- Dimensions: 5-13/16" width x 3-9/16" height x 1-1/2" depth
- Wattage: 10.8-30
- Type: Gravity, Electric, Oil, Heat Pump, Gas, Steam
- Wiring: C, R, Rc, RH, W-O/B, W2-AUX/E, Y, Y2, G, L, RAS/RAS
- Changeover: Auto, Manual
- Temp. Range: 40°F-99°F

Ordering Information

Part Number	Description
P360K-0320	Non-Programmable Wireless Thermostat Kit