

## Honeywell Thermostats

### Commercial Thermostats

#### Fan Coil/Zone Thermostats

##### SuitePRO Thermostat



#### Features:

- Simple, intuitive user interface and ease of installation
- Attractive modern styling ideal for hotels and condos
- Digital display of ambient temperature, set point, mode icons when cooling or heating relays operate, when energy savings mode is active, and fan status
- Four buttons allow manual control of system operation, fan speed, and temperature setpoint adjustment
- Versa Speed Fan Ramp Algorithm automatically adjusts Low, Medium, High fan speed
- Optional freeze protection feature that turns on heat, if necessary
- Activity sensing algorithm sets back thermostat to economy mode
- Auto fan rest option sets back fan to auto mode
- Energy savings mode -- external energy savings input from dry contact such as time switch, occupancy sensor, or hotel cardkey overrides comfort set point with selectable setback heating or cooling setpoints
- Energy savings input configurable as a normally open or normally closed dry contact
- Proportional plus integral (P+I) control algorithm for precision temperature regulation
- Selectable C or F
- Adjustable deadband, in auto changeover mode, for heat and cool control
- Adjustable maximum heating and minimum cooling set point limits
- Installer setup mode allows changes of operating parameters
- EEPROM permanently retains user settings, including setpoints, during power loss (no batteries required)
- Capability to display temperature sensor failure for easier troubleshooting
- Optional remote temperature sensor and remote pipe sensor
- Approvals, Canadian Standards Association

Part Number	Changeover	Color	Dimensions -High x Wide x Deep (Inch)	Display	Description
TB6575A1000	Manual/Auto	Premier White	3-13/16 x 5-13/16 x 1-1/8	LCD	2 or 4 Pipe Fan Coil, 120V/240V Fan Coil Thermostat,
TB6575B1000	Manual/Auto	Premier White	3-13/16 x 5-13/16 x 1-1/8	LCD	2 Pipe Fan Coil, 120V/240V Fan Coil Thermostat
TB8575A1000	Manual/Auto	Premier White	3-13/16 x 5-13/16 x 1-1/8	LCD	2 or 4 Pipe Fan Coil, 24V Fan Coil Thermostat

### Commercial Thermostats

#### MultiPRO 7000 Programmable Thermostats

##### Model TB7100A1000



#### Features:

- Large, clear display with backlight shows the current and set temperature and time--even in the dark
- Menu-driven programming make setup effortless
- Beautiful ergonomic design is smart and sophisticated to match your customers' lifestyle
- Real-time clock keeps time during power failures and automatically updates to daylight savings
- Saving Changes notification lets you know when the schedule changes have been saved
- Change reminders let you know when to replace the batteries
- Holiday Override options allow you to override the program schedule, as desired
- Speedy same--schedule programming--no need to copy multiple days
- Armchair programming allows you to remove the thermostat from the wall for programming
- Programmable or non-programmable modes
- Remote setback input for occupancy sensors or time clocks
- Versa Speed fan ramping algorithm and fan reset algorithm (fan coil and PTAC applications)
- Up to 3 fan speeds for fan coil and 2 fan speeds for PTAC applications
- Remote Indoor air sensing option (20K ohm or 10K ohm)
- Energy Star product (Title 24 energy code compliant)

#### Application

Conventional, Heat Pump, Fan Coil, and PTAC Systems

Part Number	Color	Description
TB7100A1000	Premier White	1Heat / 1Cool Programmable Commercial Thermostat, MultiPRO 7000

Compressors,  
Chillers, Condensers

Motors

Electrical

Heating  
Components

Indoor Air  
Quality

Thermostats

Oils &  
Chemicals

Accessories, Supplies  
& Commodities

Tools &  
Instruments

Refrigeration

# Thermostats

Compressors,  
Chillers, Condensers

Motors

Electrical

Heating  
Components

Indoor Air  
Quality

Thermostats

Oils &  
Chemicals

Accessories, Supplies  
& Commodities

Tools &  
Instruments

Refrigeration

## Commercial Thermostats MultiPRO 7000 Programmable Thermostats Model TB7100A1000



### Features:

- Large, clear display with backlight shows the current and set temperature and time--even in the dark
- Menu-driven programming make setup effortless
- Beautiful ergonomic design is smart and sophisticated to match your customers' lifestyle
- Real-time clock keeps time during power failures and automatically updates to daylight savings
- Saving Changes notification lets you know when the schedule changes have been saved
- Change reminders let you know when to replace the batteries
- Holiday Override options allow you to override the program schedule, as desired
- Speedy same--schedule programming--no need to copy multiple days
- Armchair programming allows you to remove the thermostat from the wall for programming
- EnergyStar Product (Title 24 energy code compliant)

### Application

- Packaged RTU
- Conventional systems
- Heat Pump Systems
- 24 Vac heating and cooling systems

Part Number	Color	Dimensions -High x Wide x Deep (Inch)	Description
TB7220U1012	Premier White	3-3/4 x 6 x 1-3/8	3 Heat / 2 Cool Programmable Commercial Thermostat

## Honeywell Thermostats Commercial Thermostats Programmable Thermostats

### Model T7351F2010



### Features:

- Typically used in buildings (including: restaurants, shopping malls, office buildings and banks) under 55,000 square feet
- For single zone rooftop units, split systems, heat pumps or hot/chilled water systems
- 365-day programming
- Two Occupied and two Not Occupied periods per day
- Individual heat and cool setpoints available for Occupied and Not Occupied periods
- P+I+D control minimizes temperature fluctuations
- Recovery ramp control automatically optimizes equipment start times based on building load
- Convenient overrides allow temporary setpoint changes
- Keypad multi-level lockout available with all models
- Remote sensor capability for temperature (including outdoor air and discharge air) and humidity sensors
- Auxiliary subbase contact typically interface with a Honeywell Economizer System (for total rooftop control integration) or act as dehumidification output
- Universal Versaguard Thermostat guards available
- Controls 24 Vac commercial single zone heating, ventilating and air conditioning (HVAC) equipment

### Approvals:

- European Community Mark (CE) Listed.
- UL 873 Recognized, NEC Class 2.
- FCC Part 15 subpart J Class A.
- cUL.

Part Number	Color	H x W x D (Inch)	Subbase H x W (Inch)	Description
T7351F2010	Trident White	4-1/2 x 6-3/4 x 2-3/16	4-1/16 x 6-9/16	Programmable Commercial stat with 3 Heat/3 Cool Stages