





ELECTRICAL

CONTACTORS

TOTALINE® CONTACTORS



Design Construction:

50/60 Hz
Meets specifications for devices up to 600 VAC in accordance with U/L bulletin no. 508 "Industrial Control Equipment"

Coil Insulation:

Standard Class B insulation.

Terminals:

Power #10-32 combination hex washer head screw, #10-32 combination hex head with pressure plate or box lug for 4 - 14 CU/AL wire.

Quick Connects - (2) 0.250 male push-ons available on each pole

Coil - (2) 0.250 male push-ons.

Covers:

Standard on 40 amp and larger.

Mounting:

Panel mount and straight thru wiring.

Application:

Designed for use in residential and commercial refrigeration, air conditioning, & heating applications.

Also:

- Water pump motors
- Blower or fans
- Compressor motors
- Resistance heating & other similar applications.

UL / CSA recognized

PART NO	POLE	AMPS	TERMINAL TYPE	COIL VAC	AUX CONTACT	LENGTH in (cm)	HEIGHT in (cm)
P282-0311	SINGLE POLE	30	(SCREW TERM. & SHUNT)	24	--	3.3 (8.38)	2.3 (5.84)
P282-0312	SINGLE POLE	30	(SCREW TERM. & SHUNT)	120	--	3.3 (8.38)	2.3 (5.84)
P282-0313	SINGLE POLE	30	(SCREW TERM. & SHUNT)	208/240	--	3.3 (8.38)	2.3 (5.84)
P282-0321	TWO POLE	30	(SCREW TERMINALS)	24	--	3.3 (8.38)	2.5 (6.35)
P282-0322	TWO POLE	30	(SCREW TERMINALS)	120	--	3.3 (8.38)	2.5 (6.35)
P282-0323	TWO POLE	30	(SCREW TERMINALS)	208/240	--	3.3 (8.38)	2.5 (6.35)
P282-0421	TWO POLE	40	(LUG TERMINALS)	24	--	3.3 (8.38)	2.6 (6.60)
P282-0422	TWO POLE	40	(LUG TERMINALS)	120	--	3.3 (8.38)	2.6 (6.60)
P282-0423	TWO POLE	40	(LUG TERMINALS)	208/240	--	3.3 (8.38)	2.6 (6.60)
P282-0331A	THREE POLE	30	(SCREW TERMINALS)	24	P282-X98220	3.4 (8.64)	2.6 (6.60)
P282-0332A	THREE POLE	30	(SCREW TERMINALS)	120	P282-X98220	3.4 (8.64)	2.6 (6.60)
P282-0333A	THREE POLE	30	(SCREW TERMINALS)	208/240	P282-X98220	3.4 (8.64)	2.6 (6.60)
P282-0431A	THREE POLE	40	(LUG TERMINALS)	24	P282-X98220	3.4 (8.64)	2.6 (6.60)
P282-0432A	THREE POLE	40	(LUG TERMINALS)	120	P282-X98220	3.4 (8.64)	2.6 (6.60)
P282-0433A	THREE POLE	40	(LUG TERMINALS)	208/240	P282-X98220	3.4 (8.64)	2.6 (6.60)
P282-0531	THREE POLE	50	(LUG TERMINALS)	24	P282-X34300	4.2 (10.67)	3.6 (9.14)
P282-0532	THREE POLE	50	(LUG TERMINALS)	120	P282-X34300	4.2 (10.67)	3.6 (9.14)
P282-0533	THREE POLE	50	(LUG TERMINALS)	208/240	P282-X34300	4.2 (10.67)	3.6 (9.14)
P282-0631	THREE POLE	60	(LUG TERMINALS)	24	P282-X34300	4.2 (10.67)	3.6 (9.14)
P282-0632	THREE POLE	60	(LUG TERMINALS)	120	P282-X34300	4.2 (10.67)	3.6 (9.14)
P282-0633	THREE POLE	60	(LUG TERMINALS)	208/240	P282-X34300	4.2 (10.67)	3.6 (9.14)
P282-0731	THREE POLE	75	(LUG TERMINALS)	24	P282-X34300	5.0	4.06
P282-0732	THREE POLE	75	(LUG TERMINALS)	120	P282-X34300	5.0	4.06
P282-0733	THREE POLE	75	(LUG TERMINALS)	208/240	P282-X34300	5.0	4.06
P282-0931	THREE POLE	90	(LUG TERMINALS)	24	P282-X34300	5.0	4.06
P282-0932	THREE POLE	90	(LUG TERMINALS)	120	P282-X34300	5.0	4.06
P282-0933	THREE POLE	90	(LUG TERMINALS)	208/240	P282-X34300	5.0	4.06