

ELECTRICAL

SPECIAL ADAPTERS

Double Male-Female Adapters



PART NO	TAB WIDTH in (mm)	QTY/PKG
P298-77250	.250 (6.35) (Piggyback)	30
P298-7MMF187	.187 (4.75) (Flat)	40
P298-7MMF250	.250 (6.35) (Flat)	40

Multi-Stack Disconnects • Vinyl Insulated



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RQDFM	.250 (6.35)	22-18 (0.5-1.0) RED	30
P298-BQDFM	.250 (6.35)	16-14 (1.5-2.5) BLUE	30

Double Male Quick Disconnects



PART NO	TAB WIDTH in (mm)	QTY/PKG
P298-DMD250	.250 (6.35)	10

Female Flag Quick Disconnects • Uninsulated



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RF187	.187 (4.75)	22-18 (0.5-1.0)	50
P298-RF250	.250 (6.35)	22-18 (0.5-1.0)	50
P298-BF187	.187 (4.75)	16-14 (1.5-2.5)	50
P298-BF250	.250 (6.35)	16-14 (1.5-2.5)	50
P298-YF250	.250 (6.35)	12-10 (4.0-6.0)	40

Female Flag Quick Disconnects • Fully Insulated Nylon



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RFFI187	.187 (4.75)	22-18 (0.5-1.0)	30
P298-RFFI250	.250 (6.35)	RED	30
P298-BFFI187	.187 (4.75)	16-14 (1.5-2.5)	30
P298-BFFI250	.250 (6.35)	BLUE	30