

# ELECTRICAL

## TERMINALS

### Quick Disconnect Terminals • Vinyl Insulated • Female



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RQDF110	.110 (2.79)	22-18 (0.5-1.0) RED	100
P298-RQDF187	.187 (4.75)	22-18 (0.5-1.0) RED	100
P298-RQDF250	.250 (6.35)	22-18 (0.5-1.0) RED	100
P298-BQDF110	.110 (2.79)	16-14 (1.5-2.5) BLUE	100
P298-BQDF187	.187 (4.75)	16-14 (1.5-2.5) BLUE	100
P298-BQDF250	.250 (6.35)	16-14 (1.5-2.5) BLUE	100
P298-YQDF250	.250 (6.35)	12-10 (4.0-6.0) YELLOW	75

### Quick Disconnect Terminals • Vinyl Insulated • Male



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RQDM187	.187 (4.75)	22-18 (0.5-1.0) RED	100
P298-RQDM250	.250 (6.35)	22-18 (0.5-1.0) RED	100
P298-BQDM187	.187 (4.75)	16-14 (1.5-2.5) BLUE	100
P298-BQDM250	.250 (6.35)	16-14 (1.5-2.5) BLUE	100
P298-YQDM250	.250 (6.35)	12-10 (4.0-6.0) YELLOW	75

### Mating Fully Insulated Quick Disconnects • Nylon Insulated • Female



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RQDFFI187	.187 (4.75)	22-18 (0.5-1.0) RED	40
P298-RQDFFI250	.250 (6.35)	22-18 (0.5-1.0) RED	40
P298-BQDFFI187	.187 (4.75)	16-14 (1.5-2.5) BLUE	40
P298-BQDFFI250	.250 (6.35)	16-14 (1.5-2.5) BLUE	40
P298-YQDFFI250	.250 (6.35)	12-10 (4.0-6.0) YELLOW	30

### Mating Fully Insulated Quick Disconnects • Nylon Insulated • Male



PART NO	TAB WIDTH in (mm)	WIRE RANGE AWG (mm2)	QTY/PKG
P298-RQDMFI187	.187 (4.75)	22-18 (0.5-1.0) RED	40
P298-RQDMFI250	.250 (6.35)	22-18 (0.5-1.0) RED	40
P298-BQDMFI187	.187 (4.75)	16-14 (1.5-2.5) BLUE	40
P298-BQDMFI250	.250 (6.35)	16-14 (1.5-2.5) BLUE	40
P298-YQDMFI250	.250 (6.35)	12-10 (4.0-6.0) YELLOW	30

### Snap Plugs • Vinyl Insulated



PART NO	WIRE RANGE AWG (mm2)	SNAP DIA		QTY/PKG
		in	(mm)	
P298-RBM157	22-18 (0.5-1.0) RED	.157	(3.99)	80
P298-RBM176	22-18 (0.5-1.0) RED	.176	(4.47)	80
P298-BBM157	16-14 (1.5-2.5) BLUE	.157	(3.99)	80
P298-BBM176	16-14 (1.5-2.5) BLUE	.176	(4.47)	80
P298-YBM157	12-10 (4.0-6.0) YELLOW	.157	(3.99)	60
P298-YBM176	12-10 (4.0-6.0) YELLOW	.176	(4.47)	60

### Snap Plug Receptacles



PART NO	WIRE RANGE AWG (mm2)	SNAP DIA		QTY/PKG
		in	(mm)	
P298-RBFFI157	22-18 (0.5-1.0) RED	.157	(3.99)	40
P298-RBFFI176	22-18 (0.5-1.0) RED	.176	(4.47)	40
P298-BBFFI157	16-14 (1.5-2.5) BLUE	.157	(3.99)	40
P298-BBFFI176	16-14 (1.5-2.5) BLUE	.176	(4.47)	40
P298-YBFFI157	12-10 (4.0-6.0) YELLOW	.157	(3.99)	30
P298-YBFFI176	12-10 (4.0-6.0) YELLOW	.176	(4.47)	30

### Double Female Snap Plug Receptacles



PART NO	RECEP DIA		QTY/PKG
	in	(mm)	
P298-DBR157	.157	(3.99)	40
P298-DBR176	.176	(4.47)	40

ELECTRICAL