


HEATING COMPONENTS

COMBINATION SINGLE STAGE DUAL GAS VALVE, REDUNDANT



- Replaces many popular brands
- Slow opening
- Single Stage
- LP kit included
- 24 volt operator
- Quick connect terminals
- Inlet and outlet pressure taps
- Off-pilot-on programmed lighting sequence for standing pilot application
- Pilot compression fitting for 1/4" O.D. tubing


PART NO	SIZE (in)	FOR USE WITH GAS TYPE		CAPACITY 1000 BTU's	PRESS IN WC
		NAT	LP		
P681-1501	1/2 x 3/4	YES	YES	130	3.5

*LP kit is included.

Replaces: Single and Dual valve standing pilot controls with rated capacity on natural gas at 130,000 BTU/HR.

HONEYWELL: V800 & VR800
 WHITE-RODGERS: 36C03-300, 36C03-330, 36C03-400 & 36C03-433
 ITT GENERAL: B57RA68, B57RF68, B57RH161, B59R02 & B59R06
 ROBERTSHAW: 700-400, 700-402 & 700-406
 STEVECO: 215-508

COMBINATION GAS CONTROLS




- Manual main and pilot gas shutoff
- Pilot gas outlet with adjustment
- Outlet gas pressure tap
- 24 volt operator
- Auto pilot shutoff and pressure regulation as noted
- Capacity: 240,000 BTU's
- Pressure set at: 3.5 @ 125m

PART NO	SIZE (in)	PRESS REG	USE NAT	WITH LP	100% SHUTOFF
EF53CK185	1/2 x 3/4	YES	YES	--	NO
EF680006*	1/2 x 3/4	YES	YES	YES	YES
EF53CK198†	1/2 x 1/2	YES	YES	--	NO
EF53CK208	1/2 x 1/2	NO	--	YES	YES
EF53CK205†	1/2 x 1/2	YES	YES	--	YES

*Kit contains EF53CK188 VALVE, Blankoff plate for converting to LP gas applications and 3/4" to 1/2" reducer bushing.

†Slow Opening



- Manual main and pilot gas shutoff
- Pilot gas outlet with adjustment
- Outlet gas pressure tap
- 24 volt operator
- Auto pilot shutoff and pressure regulation as noted
- Pressure set at: 3.5 @ 150m (EF33CB181)
 11 @ 125m (EF53CK248)

PART NO	SIZE (in)	CAPACITY 1000 BTU's	PRESS REG	USE NAT	WITH LP	100% SHUTOFF
EF33CB181	1/2 x 1/2	225	YES	YES	--	NO
EF53CK248	1/4 x 3/4	486	YES	--	YES	YES

HEATING COMPONENTS