

# HEATING COMPONENTS

## COMBINATION GAS CONTROLS




- Manual main and pilot gas shutoff
- Natural gas
- Pilot outlet with adjustment
- Outlet gas pressure tap
- 24 volt operator
- Pressure regulator
- Heat motor gives time delay
- Size 1/2" x 3/4", has pressure regulator, use with natural gas, pressure set at 3.5 @ 125M
- Capacity: 164,000 BTU's
- Non 100% shutoff
- Includes 3/4" x 1/2" reducer bushing

**PART NO**

EF53CK198

## COMBINATION DUAL VALVE GAS CONTROLS



- Dual main electric valves – redundant
- Manual main gas shutoff
- I.I.D. system applicable
- Pilot gas adjustment
- Pressure regulator
- Outlet gas pressure tap
- Natural gas
- 24 volt operator

**FOR USE WITH GAS TYPE**


PART NO	SIZE (in)	NAT	LP	CAPACITY 1000 BTU's	PRESS IN WC
EF32CB212	1/2 x 3/4	YES	--	130	3.5

Similar models to RCD P/N EF33CZ206 with slight changes:

- Size 1/2" x 1/2"
- Capacity 179,000 BTU's

**PART NO**

EF33CZ209




- Dual main electric valves – redundant
- Manual main gas shutoff
- 24 volt operator
- Adjustable pilot gas flow
- Outlet gas pressure tap
- Pressure regulator
- Natural gas
- I.I.D. system applicable

PART NO	CAPACITY 1000 BTU's	PRESS SET AT
EF680007	250	3.5

**NOTE:** Package includes EF32CB210 valve and 3/4" to 1/2" reducer bushing.

## COMBINATION TWO STAGE GAS CONTROLS




- Pre-selected first stage firing rate
- Adjustable high fire rate
- 24 volt operator
- Manual main gas shutoff
- Pilot gas adjustment
- Outlet gas pressure tap
- Pressure regulator

**FOR USE WITH GAS TYPE**

**PRESS IN**

PART NO	SIZE (in)	NAT	LP	CAPACITY 1000 BTU's	WCLO	WCHI	100% SHUTOFF
EF680016	3/4 x 3/4	YES	--	335	1.3	3.5	NO



### Universal electronic ignition gas valve

- Control includes manual valve, two automatic operators, pressure regulators, pilot adjustment, pilot plug and ignition adapter.
- Highest capacity (415,000 BTU MAX. REG., NG) of any electronic ignition valve in the industry.
- Replaces virtually any IP, his, or DSI gas control.
- For use with natural or manufactured gas or LP gas.
- Honeywell part no: VR8345M4302

**PART NO**

P681-VR8345M

## Continuous pilot dual automatic valve combination gas controls

- Controls include safety shutoff, manual valve, two automatic operators, pressure regulator and pilot adjustment.
- Replaces over 95 percent of the standing pilot gas valves; maximum capacity rating is 150% of the competitive valves.
- Meets 1979 ANSI i standards for redundancy in gas valve operation.

PART NO	HONEYWELL PART NO
P660-VR83A3500	VR8300A3500
P660-VR83A3518	VR8300A3518
P660-VR83A4508	VR8300A4508
P660-VR83A4516	VR8300A4516